



**Technical specification:**

Rated voltage: 30 V  
IEC 61076-2-101  
Current rating: 2 A at 40°C  
IEC 61076-2-101  
Insulation resistance: >=100 MΩ  
IEC 60512  
Pollution degree: 3/2  
IEC 60664-1  
Degree of protection: IP 67, in mated condition  
IEC 60529  
Temperature range: -30°C ... +85°C  
EN 60512-11-10  
-40°C ... +85°C  
EN 60512-11-4  
Mating cycles: >=100  
IEC 60512-9a

**Materials:**

Contact: CuZn, Ni b / Au 0,2 gal.  
Contact carrier: PA GF, UL 94 V-0  
Sealing: FPM / NBR  
Socket housing: CuZn, nickel plated  
Shroud: spring steel, nickel plated

**Installation specification:**

recommended torque: 0,8-1 Nm  
Conec installation tool: Torque wrench: 36-000200  
Insert across flats 14: 36-000370  
Insert across flats 15: 36-000320

Part no:	Description:	Pos	Note:
43-02739	SAL - 12 - FKHW8	8	
43-02740	SAL - 12S - FKHW8	8	with shroud

DO NOT ALTER CAD DRAWING BY HAND

RoHS & REACH compliant

Index: a 11.05.16 fro Ä4884  
data sheet revised, width across flats was 15  
ist 14

general tolerance:

0	± 0,50mm
0,0	± 0,25mm
0,00	± 0,10mm
*	± 1,5°

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND  
MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

dim. in mm

	date	name
drawn	07.01.16	Böckeler
appd.	07.01.16	Fromm

**CONEC**®

title:  
**Female socket M12x1 angled,  
backmounting, dip solder**

dwg no:  
**43K1A3071**

part no:  
**see table**